

# MAJAR



L'accessoire essentiel

## Olympe



### OLYMPE 6000

For sports fields, green spaces, golfs, agricultural exploitations...

### Options

Connection kit and extension diameter 45 mm, Length 12,5 or 15m, sand filter.

## Sprinkler with automatic reel

### FUNCTION OLYMPE 6000

Easy and fast starting up.  
Motorisation by turbine and reducer (no water discharge). Speed adjustment with bypass.  
Anti-derailment device. Cable guide. Automatic limit switch-off in the end position with membrane valve .

### STRUCTURE OLYMPE 6000

Welded tubular chassis  
Reversible tiller: towed or hand pushed.  
Tyres 16/650 x 8 ball bearings  
Direction tyre: Ø 275 x 100 roller bearings.  
Sprinkler trolley 3 tyres with adjustable direction tyre.

### FINISHING OLYMPE 6000

Two polyethylene housing shields for safety and invulnerability. High corrosion protection.

under the hood



towed



manual



## OLYMPE 2300

For sports fields, green spaces, vegetable gardens, greenhouses, tree nurseries, horticulture...



### Options

Connection kit and extension diameter 35 mm, Length 12,5 or 25m.

### FUNCTION OLYMPE 2300

Motorisation by double-action cylinder protected by a filter. Reed speed adjustment. Cable guide. Automatical stop at end position

### CHARACTERISTICS

MODEL	Ø (mm)	Hose length (m)	Minimal pressure (bar)	Reed Speed (m/h)	Weight (Kg)	Width (Kg)	Height (cm)
6000	40	120	3	0/50	315	114	150
2300	25	90	3	0/45	80	6	

### PERFORMANCES

MODEL	Ø nozzle (mm)	Winding pressure (bar)	Sprinkler pressure (bar)	Reach (m)	Debit (m/h)	Speed for 5 mm (m/h*)	Speed for 10 mm (m/h*)	Maximal speed (m/h)
6000 Sprinkler KOMET R20	7	3,0	2,6	18,00	2,80	/	11,0	18
		4,0	3,4	19,00	3,20	/	13,0	22
		5,0	4,0	20,00	3,60	/	13,5	26
	8	3,0	2,2	17,50	3,50	/	12,0	24
		4,0	3,0	18,00	4,10	/	14,0	30
		5,0	3,5	19,00	4,40	/	15,0	35
	10	3,0	1,7	17,00	4,60	/	15,0	28
		4,0	2,4	18,50	5,80	/	16,0	30
		5,0	2,8	20,00	6,10	/	17,0	42
2300 F33 Sprinkler ROLLAND 175	4	3,0	2,0	12,00	0,86	8,1	/	/
		4,0	3,0	13,00	1,00	10,2	/	/
		5,0	4,0	14,00	1,20	11,9	/	/
	5	3,1	2,0	14,00	1,20	11,4	/	/
		4,6	3,0	14,50	1,50	13,8	/	/
		6,0	4,0	15,00	1,70	15,1	/	/
	6	3,1	2,0	15,00	1,80	13,5	/	/
		4,6	3,0	16,00	2,20	14,5	/	/
		6,0	4,0	17,00	2,60	16,7	/	/
2300 Sprinkler KOMET R20	6	5,0	3,0	18,00	2,29	17,0	/	/
		5,5	3,5	18,00	2,48	17,4	/	/
		6,0	4,0	20,00	2,65	17,7	/	/

\*winding speed: meter per hour for irrigation of 10mm (OLYMPE 6000); for 5mm (OLYMPE 2300)