

MAJAR



L'accessoire essentiel



IMHEM15D

RIDGER

Ref	Working width	Tines	Weight Kg	HP
■ Carried ridger 15 tines				
IMHEM15D	110 cm or 125	15	35	10/20

Linkage n°1
1 element, 2 assemblies possible
Square tines 20mm interchangeable, length 20 cm



HEM30D

HARROW

Ref	Working width	Tines	Weight Kg	HP
■ Carried harrow 20 tines				
HEM20D	130 cm	20	87	12/35
■ Carried harrow 30 tines				
HEM30D	180 cm	30	107	12/35

Linkage n°1
2 independent suspended elements
Square tines 20 mm interchangeable, length 20 cm



V7D



CM7R



CM7B

CULTIVATOR

Ideal to work on ploughed soil

Ref	Adjustable	Working width	Weight Kg	HP
■ Adjustable cultivator, linkage n°1, supple tines				
V7D	yes	80/120 cm	90	13/20
V9D	yes	90/150 cm	100	16/25
V11D	yes	100/180 cm	120	18/35

Options :
ROUECULTMIC Pair of depth control wheels

Ref	Adjustable	Working width	Tines	Weight Kg	HP
■ Fixed cultivator, linkage n°1					
CM7	no	80 cm	Supple	70	13/20
CM9	no	120 cm	Supple	80	15/30
CM11	no	150 cm	Supple	92	18/35

Options :
ROUECULTMIC Pair of depth control wheels

Ref	Adjustable	Working width	Tines	Weight Kg	HP
■ Fixed cultivator, linkage n°1					
CM7R	no	90 cm	Stiff	50	13/20
CM7B	no	110 cm wing shares		50	13/20

Options :
ROUECULTMIC Pair of depth control wheels

Tools for compact tractor

MAJAR

L'accessoire essentiel



CM9DS + ROUE CULTMIC

PROFESSIONAL CULTIVATOR

Ref	Working width	Tines	Weight Kg	HP
■ Professional cultivator, square tines 20 mm Double turn				
CM5DS	85/100 cm	5	73	20/35
CM7DS	110/130 cm	7	105	30/60
CM9DS	150/170 cm	9	120	35/70

Options :

- ROUECULTMIC** pair of depth control wheels
EXT2DS Extension to 7 or 9 tines



CM7TR + ROUE CMTR

TILLER CULTIVATOR WITH SPRINGS

To prepare the soil before rotary machine

Ref	Working width	Tines	Weight Kg	HP
-----	---------------	-------	-----------	----

■ Tiller cultivator with springs

CM5TR	80/120 cm	5	170	25/50
CM7TR	120/170 cm	7	230	30/70

Stiff chassis machine-welded square tube 60 mm, thickness 5 mm. Heavy tines height 60 cm with reversible over-stamped share 70 x 7.

Sliding tine support

Options :

ROUECMTR pair of depth control wheels

Frame Tool Carrier for Microtracteur



S02040

SUBSOILER

Ref	Weight Kg	HP
■ Subsoiler with drainer		
S02040	60	12/35
Linkage n°1. Working depth 20 – 40 cm		



CPODEC5D

SOIL LOOSENER

Ref	Working width	Tines	Weight Kg	HP
■ Soil loosener				
DEC3D	150 cm	3	55	17/30
DEC5D	150 cm	5	65	22/35

Linkage n°1. Working depth 20 cm



CPO3BRI

FRAME TOOL CARRIER

Ref	Working width	Number tines	Weight Kg	HP
■ Frame tool-carrier				
CPO1BRI	75 cm	1	30	12/35
CPO2BRI	150 cm	2	43	12/35
CPO3BRI	150 cm	3	46	15/35

Linkage n°1. To equip with potato digger or ridger



BUT3



BUT4

REINFORCED MICRO RIDGER

Ref	Working width	Weight Kg
■ Ridger with adjustable mouldboard and counterfoil		
BUT3 Rod 50x15 included	35/50 cm	14
BUT4 Rod 50x15 included	40/64 cm	15

To mount on CPO (works on 1 – 3 rows)



APMICRO



APMICRO2

POTATO DIGGER

Ref	Working width	Weight Kg
■ Reinforced potato digger		
APMICRO	22/44 cm	10
APMICRO2	17/44 cm	12

Rod 50 x 14

To mount on CPO (works on 1 – 3 rows)

MAJAR

1, Route de Montréal - CS 30074 - 11890 Carcassonne Cedex 9

E-mail: commercial@majar.fr - Tél.: 04 68 72 83 11 - Fax: 04 68 72 51 61