

# MAJAR



*L'accessoire essentiel*



## Tools for Quad



**OXLN150**

## GRADER BLADE / SNOW PLOUGH

### ADJUSTABLE BLADE IN SHEETS 4 MM

Anvil-blade 8 mm. adjustment angle 0° 20° 30° fast indexing or 0° +20° +40° +50° on right or left according to lever position. Adjustable side bases. Safety spring. Quick fastening with 4 pins.

**Options** ..... Rubber snow band 80 x 15 mm + support+bolts

<b>WORKING WIDTH 130 cm</b>	42 kg	<b>Ref OXLN130</b>
<b>WORKING WIDTH 150 cm</b>	45 kg	<b>Ref OXLN150</b>
<b>WORKING WIDTH 185 cm</b>	51 kg	<b>Ref OXLN185</b>



**OXROULES130**

## SMOOTH ROLLS

### WORKING WIDTH 130 cm

**Possibility to ballast with water** (150 l.)

Ø 40 cm, thickness 6 mm, overall 143 cm

Equipped with adjustable mud scraper

Dragged, ball hitch Ø 50

Weight 146 kg..... **Ref OXROULES130**

### WORKING WIDTH 180 cm

**NO BALLAST POSSIBLE**

Ø 40 cm, thickness 6 mm, overall 193 cm

Equipped with adjustable mud scraper

Dragged, ball hitch Ø 50

Weight 200 kg..... **Ref OXROULI180**



**OXEMTG260**

## PROFESSIONAL SPREADER

**Ref OXEMTG260**

Fertilizer spreading for cultivations or salt for roadways (galvanized case optional). Very robust design

Ball hitch Ø 50 or ring Ø 32,

Spread selector right-left and agitator included, drive can be disengaged.

Towing speed 25 km/h

### High stability :

Tub width 108 cm, way 141 cm (154 cm overall)

Delivered with agrarian wheels, lawn wheels optional. Weight 120 kg

Capacity (l)	Working width (m)	Working speed (km/h)	Ø tub (cm)	Tub height (cm)
260	6/18	6 à 12	120	135

### Options :

- galvanized tub OXEMTG260..... **CUVGQUAD**
- tub closing with sheeting..... **BACHEMTGQUAD**
- lawn wheels..... **ROUEGEMTG260**
- articulated agitator – length 36 cm..... **ZEM3PGR01H**
- fixed salt agitator..... **EMTGKITSEL**
- spreader limiter..... **LEPG260**



OXRM412



OXRPR717



OXRPR820G

The boggie versions suite for uneven terrain with its balancing axles system and low pressure pneumatics.



OXCP817G + OXCPC1217



OXCP717 + OXCPR517

## MONOBLOC TRAILER

Compact design and excellent manoeuvrability

Wheels under chassis – tipping. Removable tipping back buffer  
 Ball coupling Ø 50. Wheels Ø 463 x 224 ..... 18 x 9.50-8.....  
 ...4 ply rating ....0.4 bars  
 Case 120 x 100 x 40 cm – Overall width 108 cm  
 Payload 400 kg – Weight 104 kg

- Wheel 18 x 9.50-8 ..... 082585

## PLATEFORME WITH SIDEBOARD

Hinged and removable sideboards for change

Wheel under chassis – tipping – removable back buffer top and bottom articulated – front buffer removable – back posts – ball coupling Ø 50

### SINGLE AXLE Case 170 x 120 x 35 cm

Payload 700 kg - Weight 190 kg ..... OXRPR717  
 Wheels 21 x 9-10 ..... 6 ply rating ..... 3 bars

### BOGGIE Case 170 x 120 x 35 cm

Payload 800 kg - Weight 230 kg ..... OXRPR817G  
 Wheels 18 x 9.50-8 ..... 4 ply rating ..... 0,4 bars

### SINGLE AXLE Case 200 x 120 x 35 cm

Payload 700 kg - Weight 200 kg ..... OXRPR720  
 Wheels 21 x 9-10 ..... 6 ply rating ..... 3 bars

### BOGGIE Caisse 200 x 120 x 35 cm

Payload 800 kg - Weight 240 kg ..... OXRPR820G  
 Wheels 18 x 9.50-8 ..... 4 ply rating ..... 0,4 bars

- Wheel single axle 21 x 9-10 right ..... 082586D
- Wheel single axle 21 x 9-10 left ..... 082586G
- Wheel boggie 18 x 9.50-8 right ..... 082588D
- Wheel boggie 18 x 9.50-8 left ..... 082588G

## SUPPORT FRAME

Frame 60 x 60 - tipping - ball coupling Ø 50

### SINGLE AXLE Chassis 170 x 57 cm

Payload 700 kg - Weight 90 kg ..... OXCP717  
 Wheels 21 x 9-10 ..... 6 ply rating ..... 3 bars

### BOGGIE Chassis 170 x 57 cm

Payload 800 kg - Weight 126 kg ..... OXCP817G  
 Wheels 18 x 9.50-8 ..... 4 plis ..... 0,4 bars

Options :

- Case 170 x 112 to fix on the support chassis ..... OXCPC1217  
 Weight 70 kg
- 8 stanchions height 50 cm - Ø 42 mm ..... OXCPR517  
 Weight 25 kg
- Wheel single axle 21 x 9-10 right ..... 082586D
- Wheel single axle 21 x 9-10 left ..... 082586G
- Wheel boggie 18 x 9.50-8 right ..... 082588D
- Wheel boggie 18 x 9.50-8 left ..... 082588G





OXRPR515



RMT900B

## AGRICULTURAL TIPPING TRAILER

Wheel under chassis – Back buffer and sideboards  
Removable and hinged – Front buffer removable – Ball coupling  
Ø50 – Tipping – Without parking brake – With reflector signs –  
Serial stand.

**SINGLE AXLE** Case 150 x 100 x 28 cm  
Payload 500 kg - Weight 120 kg ..... **OXRPR515**  
Wheels 18 x 9.50 ..... 8 plis ..... 0,4 bars

Option :

Mesh extension panel height 50 cm - Weight 38 kg .. **RGM515**

**SINGLE AXLE** Case 200 x 120 x 35 cm  
Payload 1000 kg - Weight 145 kg ..... **RMT900B**  
Wheels 600 x 9 ..... 10 plis ..... 6 bars

Option :

Mesh extension panel height 100 cm - Weight 75 kg .. **RGM1020**