

Polyvalent Crushing 20 – 45 HP



Embankment Flail Mower RBML 115AC/130AC/155AC
 Microtractor 20 - 45 HP with power grip = 540 tr/min
 Minimum weight 700 kg, equipped with 2 double acting control valves

Working width 115, 130 or 155 cm – 3 point linkage cat.1
 Intended for small tractors due to the reduced weight and the tube linkage Ø 76mm with narrow hitch (interior side of arms 62 cm)
 Y-knives width 40 mm thickness 5 mm
 Delivered with cardan shaft with shearbolt clutch - Gearbox with freewheel
 Cutting height adjustable: 0 - 11cm depending on knife type (Y, hammers or paddles)
 Oversized tilting joint Ø50 mm mounted on wear ring

The advantages :

Substantial fuel savings due to the rotor design

Rotor with helical position: even drive without effort for optimal crush. Big rotor tube : cutting rigidity and inertia, electronic balancing after assembly of knives. Reduced energy consumption and CO2-emission

High rotation speed: rotation 2500 tr/min, cutting speed of 42m/s for a perfect cut and crush

System to avoid grass jam: no risk of grass winding around the roll

Curved chassis: the chassis form and the particular disposition of the back roll optimize the ventilation, ejection and self-cleaning of the roll **Armoured sheet thickness 3 mm on model 155**

Back tyre conceived especially to resist lateral movement and to protect the gearbox from gras jam and projections

Large opening : allows to swallow the vegetation without flatten

Cylinder hoses with coupling 1/2" and valves for speed setting

Locking pin of tilting joint to secure the operations of transport and maintenance, permits also to use the device on flat ground on a tractor with only one control valve

Drive: 2 trapezoidal belts, adjustable tension can be controlled easily

Security, ergonomic: lateral deflectors adjustable, front flaps anti-projection

Mechanical breakaway with pendulum rod to avoid obstacles

lubrication accessible without disassembly

	(CV)	Number of tools		Overall dimensions L x l x h (cm)	Weight (kg)
		"Y"	Paddles - Hammers		
VRBML115AC	20/35 CV	40	20	150 x 134 x 90	220
VRBML130AC	25/45 CV	44	22	150 x 148 x 90	230
VRBML155AC	30/45 CV	52	26	150 x 172 x 90	250

Serial Assembly with Y-knives, option assembly with paddles or hammers



