

**Intense Crushing
25 - 60 HP**

Embankment Flail Mower RBRM 115AC/130AC/155AC
 Microtractor 25 - 60 HP with power grip 540 tr/min
 Minimum weight 700 kg, equipped with 2 double acting control valves



Working width 115, 130 or 155 cm – 3 point linkage cat.1
 Intended for small tractors due to the reduced weight and the tube linkage Ø 76mm with narrow hitch (interior side of arms 62 cm)
 Y-knives width 40 mm thickness 5 mm
 Delivered with cardan shaft - Boitier avec roue libre incorporée.
 Cutting height adjustable from 0 to 11cm depending on knife type (Y, hammers or paddles)
 Oversized tilting joint Ø50 mm mounted on wear ring

The advantages:

Helical steel gearbox with free wheel: *Transmission of efforts without noise or vibration*

Substantial fuel savings due to the rotor design

Rotor with helical position: *even drive effort for optimal crush big rotor tube : cutting rigidity and inertia, electronic balancing after assembly of knives. Reduced energy consumption and CO2-emission*

High rotation speed: *rotation 2500 tr/min, cutting speed of 42m/s for a perfect cut and crush*

System to avoid gras jam: *no risque of gras winding around the roll*

Curved chassis: *the chassis form and the particular disposition of the back roll potimize the ventilation, ejection and self-cleaning of the roll. Armoured sheet thickness 3 mm on model 155*

Back roll: *especially conceived to resist lateral moves and to protect from projections*

Large opening: *allows to swallow the vegetation without flatten*

Drive: 3 trapezoidal belts, adjustable tension can be controlled easily

Security, ergonomic: lateral deflectors adjustable, front flaps anti-projection, large patin de protection du carter courroie, châssis avec trous pour manilles de manutention.

Bielle d'attelage pendulaire pour un effacement en cas d'obstacle.

Lubrication accessible without disassembly

| | (CV) | Number of tools | | Overall dimensions | Weight (kg) |
|------------|-------|-----------------|-------------------|--------------------|-------------|
| | | "Y" | Paddles - Hammers | L x l x h (cm) | |
| VRBRM115AC | 25/50 | 40 | 20 | 150 x 134 x 90 | 230 |
| VRBRM130AC | 25/60 | 44 | 22 | 150 x 148 x 90 | 240 |
| VRBRM155AC | 30/60 | 52 | 26 | 150 x 172 x 90 | 255 |

Serial Assembly with Y-knives, option assembly with paddles or hammers



